Implementation of Vehicle Navigation System using GNSS, INS, Odometer and Barometer

Jungi Park, DongSun Lee, Chansik Park[†]

Department of Electronics Engineering, Chungbuk National University, Cheongju 28644, Korea

ABSTRACT

In this study, a Global Navigation Satellite System (GNSS) / Inertial Navigation System (INS) / odometer / barometer integrated navigation system that uses a commercial navigation device including Micro Electro Mechanical Systems (MEMS) accelerometer and gyroscope in addition to GNSS, odometer information obtained from a vehicle, and a separate MEMS barometer sensor was implemented, and the performance was verified. In the case of GNSS and GNSS/INS integrated navigation system that are generally used in a navigation device, the performance would deteriorate in areas where GNSS signals are not available. Therefore, an integrated navigation system that calculates a better navigation solution in areas where GNSS signals are not available compared to general GNSS/INS by correcting the velocity error of GNSS/INS using an odometer and by correcting the cumulative altitude error of GNSS/INS using a barometer was suggested. To verify the performance of the navigation system, a commercial navigation device (Softman, Hyundai Mnsoft, http://www.hyundai-mnsoft.com) and a barometer sensor (ST Company) were installed at a vehicle, and an actual driving test was performed. To examine the performance of the algorithm, the navigation solutions of general GNSS/INS and the GNSS/INS/odometer/barometer integrated navigation system were compared in an area where GNSS signals are not available. As a result, a navigation solution that has a smaller position error than that of GNSS/INS could be obtained in the area where GNSS signals are not available.

Keywords: INS, integrated navigation system, odometer, barometer

1. INTRODUCTION

With the introduction of smartphones and smartwatches, the demand for a vehicle navigation system that is linked with personal position service has increased, and thus the importance of a navigation device has continuously increased. In particular, with the increased interest in autonomous vehicles due to the development of Advanced Driver Assistant System (ADAS), existing vehicle navigation devices based on Global Positioning System (GPS) have developed into navigation devices with higher accuracy and wider availability, which are complex navigation systems

Received May 13, 2015 Revised July 20, 2015 Accepted July 22, 2015 [†]Corresponding Author

E-mail: chansp@cbnu.ac.kr Tel: +82-43-261-3259 Fax: +82-43-261-2386 integrated with various sensors such as inertial sensor, camera, and Light Detection and Ranging (LIDAR).

Global Navigation Satellite System (GNSS) is a positioning system that precisely calculates the position of a user based on a number of satellites orbiting around the Earth. GNSS can be used for a long time since it shows no divergence of error depending on the usage time, and is capable of precise positioning around the globe. On the other hand, the reliability of position measurements could vary depending on external factors since signals transmitted from the satellites are very weak, and it is difficult to obtain a navigation solution in tunnels and underground passages where signals cannot be received (Akim & Tuchin 2003).

Inertial Navigation System (INS) provides the position, velocity, and attitude of a vehicle using inertial information measured by a gyroscope and an accelerometer, and it is an independent system that is not affected by external environments. Also, it has high sampling frequency, and thus necessary information can be continuously provided and an accurate navigation solution can be calculated in a short time. On the other hand, the error of each sensor accumulates through integration, and increases abruptly as time passes. Thus, to compensate accumulating error, it is generally used in combination with a sensor that is free from cumulative error. A representative device that is used in combination with INS includes GNSS (Trtterton & Weston 2004).

As mentioned above, GNSS and INS have complementary characteristics. Accordingly, if a system is based on INS, which can efficiently measure dynamic characteristics, and uses GNSS as an auxiliary sensor, a complex navigation system that can maintain accuracy without divergence for a long time by tracking the change of a fast-moving body in environments with good GNSS signals can be implemented.

However, unlike the environments for ships and aircraft, areas with poor GNSS signals occur frequently in the environments for vehicle driving. When more than four GNSS signals are not received in downtown area, a tightly coupled GNSS/INS integrated navigation system is organized to correct the navigation solution of a vehicle (Angrisano 2010), but this cannot be used in tunnels, underground parking lots, and underground roads where no GNSS signals can be received.

To overcome this, methods for correcting the error of INS in areas where GNSS signals are not available using additional sensors installed at a vehicle have been actively studied, and representative methods include a method based on the odometer of a vehicle and a method based on the image information of a vehicle. A method based on image information can replace GNSS by figuring out the position of a vehicle through recognizing and utilizing the position of traffic signs on the roadside, but the use of the method is limited because there are sections with no traffic sign on the actual roadside (Bevly & Cobb 2010). An odometer is a device that is basically installed at an actual vehicle, and it can be used for correcting the velocity error that occurs from the integration of a low-priced Micro Electro Mechanical Systems (MEMS) accelerometer. However, the vehicle velocity information of an odometer also includes error. Accordingly, if the final position is calculated by integrating the velocity information corrected based on an odometer, cumulative error occurs, and thus an additional sensor for correcting this is required (Kim & Hwang 2013).

In this study, a loosely coupled GNSS/INS/odometer/ barometer integrated navigation algorithm that combined GNSS receiver and MEMS accelerometer and gyroscope installed at a commercial navigation device, an odometer of a vehicle, and a barometer was suggested, and the performance was verified through comparison with general GNSS/INS by conducting an actual vehicle driving test.

2. GNSS/INS/ODOMETER/BAROMETER INTEGRATED NAVIGATION SYSTEM

The navigation algorithm of INS calculates information such as the position, velocity, and attitude of a vehicle using the outputs of a gyroscope and an accelerometer, and it is broadly divided into an initial alignment algorithm and a navigation calculation algorithm.

Initial alignment is to obtain the initial attitude of the body frame relative to the navigation frame from the sensor measurements of an accelerometer and a gyroscope before a navigation system enters a normal navigation mode. Initial attitude error is one of the major navigation error factors, and is mostly caused by the random bias error of a gyroscope and an accelerometer. If error occurs in the initial attitude, the error accumulates continuously, and thus, the accuracy of initial alignment has a large effect on the performance of a navigation system.

Initial coarse alignment is to obtain the initial coordinate transformation matrix and initial attitude angle between the navigation frame and the body frame using the measurements of an accelerometer and a gyroscope when a vehicle is at a standstill, and it was implemented based on a reference (Park et al. 1998).

In the case of attitude calculation for a navigation calculation algorithm, a method based on quaternion and a method based on direction cosine matrix are used in general. It is known that an attitude calculation algorithm using quaternion has the smallest numerical error. This algorithm calculates the attitude of a vehicle using four parameters, and it has the advantages of easy normalization and a small amount of calculation. The coordinate transformation matrix was continuously calculated using the initial attitude information calculated through the initial coarse alignment, gyroscope measurements, and quaternion, and it was implemented based on references (Jeon & Lee 1988, Kong 2000).

INS error varies significantly depending on the performances of an accelerometer and a gyroscope, and it is known that for a low-priced inertial sensor generally used in automotive application, a correct solution cannot be calculated because a navigation solution diverges in a very short time. The factors that have the largest effect on INS error include acceleration bias error and the angle random walk of a gyroscope, and the performance of the inertial sensor used in the present study was examined through calculation based on a reference (Park 2004).

To overcome the cumulative error of INS, a highpriced inertial sensor needs to be used, or a method for correcting the diverging cumulative error is needed; and a representative method includes combination with GNSS. The combination methods are broadly classified into a tightly coupled method and a loosely coupled method. The loosely coupled method performs combination at the system level of INS and GNSS, and thus, it has the advantages of short calculation time and simple measurement model. On the other hand, the method cannot provide an accurate navigation solution when the number of visible satellites is insufficient or when it is operated with large dynamic characteristics. However, in this study, the loosely coupled method was used since there was a limitation that a navigation solution calculated by a receiver should be used (Godha 2006).

To organize the Kalman filter for the estimation and correction of error, a navigation error model and an inertial sensor error model need to be established first. The navigation error model was obtained through a perturbation method; and for the sensor error model, random errors among the errors of the gyroscope and the accelerometer were modeled using the random processor of random constant and white noise. The implementation was based on a reference (Godha 2006). When the INS error model is used to establish a GNSS/INS integrated navigation system, the system model of the navigation system can be obtained based on references (Nassar 2003, Christensen & Fogh 2008).

A GNSS/INS integrated navigation system corrects the error of INS based on the position and velocity information of GNSS; and in environments where GNSS signals cannot be received for a long time, the error of INS cannot be corrected. Therefore, a method that can correct the error of INS in areas where GNSS signals are not available is required.

To supplement the disadvantage of a GNSS/INS integrated navigation system, error could be corrected using a separate sensor; and in the case of a vehicle, navigation error can be reduced using odometer information. The position error of INS is affected by velocity error and attitude error; and when the attitude error is larger than the velocity error, the position error increases as time passes. To reduce this position error, the error of INS navigation solution can be reduced by correcting the attitude error and velocity error of INS through establishing a velocity correction system using an odometer. In addition, the altitude position information of GNSS has lower accuracy than horizontal position information; and INS has a problem of diverging altitude information due to the accumulation of error in areas where the reception of GNSS signals is difficult. To overcome this, an altitude correction system that corrects altitude error by installing a separate barometer sensor also needs to be established. Therefore, a GNSS/INS/odometer/ barometer integrated navigation system using an odometer and a barometer is needed.

An odometer uses an encoder sensor installed at the wheel of a vehicle. An encoder generates pulse signals depending on the rotation of the wheel of a vehicle, and the velocity of the vehicle is measured based on the number of rotations for the wheel. The velocity of the vehicle (m/s) is calculated using Eq. (1).

$$V_{x} = \frac{N \times Sf_{x}}{\Delta t}$$
(1)

where N is the number of pulses for the encoder, Sf_N is the conversion factor for the encoder, and V_{SE} is the measured velocity of the vehicle. The major error factors of an odometer include conversion factor error and non-alignment error.

The velocity of the vehicle in the moving direction, V_{SE} (m/s), can be expressed by the output of the odometer, $V_{xo'}$ and the conversion factor error, $K_{xo'}$ as shown in Eq. (2) (Seo et al. 2006). In this regard, K_{xo} refers to the error output of the conversion factor, $Sf_{N'}$ which is used to convert the encoder output of the vehicle into a velocity.

$$V_{xv} = V_{xo} + K_{xo}V_{xo}$$
(2)

Eq. (2) can be expressed as Eq. (3) based on the body frame.

$$V_{xv} = \begin{bmatrix} v_{xv} \\ 0 \\ 0 \end{bmatrix} = \begin{bmatrix} 1 + K_{xo} & 0 & 0 \\ 0 & 1 & 0 \\ 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} v_{xo} \\ 0 \\ 0 \end{bmatrix} = KV_{xo}$$
(3)

The non-alignment error of an odometer occurs because the axis of the odometer is not consistent with the x-axis of the body frame, and there are non-alignment errors of pitch angle and yaw angle. When the axis of the odometer is marked as the o-axis, the coordinate transformation matrix into the body frame b, C_{a}^{b} can be expressed as Eq. (4).

$$C_{o}^{b} = \begin{bmatrix} \cos \delta \theta & 0 & \sin \delta \theta \\ 0 & 1 & 0 \\ -\sin \delta \theta & 0 & \cos \delta \theta \end{bmatrix} \begin{bmatrix} \cos \delta \psi & -\sin \delta \psi & 0 \\ \sin \delta \psi & \cos \delta \psi & 0 \\ 0 & 0 & 1 \end{bmatrix}$$
(4)

where $\delta\psi$ and $\delta\theta$ are the non-alignment errors of the yaw angle and the pitch angle, respectively. When Taylor series expansions are obtained and the second-order term or above is ignored, they can be expressed as Eq. (5).

$$C_{o}^{b} = \begin{bmatrix} 1 & -\delta\psi & \delta\theta \\ \delta\psi & 1 & 0 \\ -\delta\theta & 0 & 1 \end{bmatrix}$$
(5)

Using the elements of conversion factor error and nonalignment errors which are the error factors of the above odometer, an odometer error model in the navigation frame can be derived. The velocity in the navigation frame considering the error can be expressed as Eq. (6).

$$\hat{V}^{n} = C_{b}^{n}C_{o}^{b}KV_{xo} = C_{b}^{n}\begin{bmatrix} 1+K_{xo} & -\delta\psi & \delta\theta\\ \delta\psi & 1 & 0\\ -\delta\theta & 0 & 1 \end{bmatrix}\begin{bmatrix} v_{xo}\\ 0\\ 0\end{bmatrix}$$
(6)

The measured velocity of the odometer in the navigation frame, V^n , satisfies the relationship of the multiplication of the odometer output and the coordinate transformation matrix from the body frame to the navigation frame, C_{bn}^n and thus, the velocity error model can be expressed as Eq. (7).

$$\delta V^{n} = \hat{V}^{n} - V^{n} = C_{b}^{n} \begin{bmatrix} K_{xo} v_{xo} \\ \delta \psi v_{xo} \\ -\delta \theta v \end{bmatrix}$$
(7)

A barometer is a sensor for measuring pressure, and it provides the altitude information of navigation by converting the measured atmospheric pressure into a relative altitude. It has high long-term navigation stability, but error could occur due to external environments such as the changes in temperature and pressure.

As for the navigation algorithm of a barometer, initially measured pressure is defined as a relative altitude of '0'm, and altitude difference from the initial altitude is provided by converting the pressure measured during driving into a relative altitude. The method for calculating the relative altitude can be expressed as Eq. (8).

$$\Delta h = \frac{T_0}{T_{gradient}} \left(1 - \left(\frac{P_s}{P_{s0}}\right)^{T_{gradient}\frac{G_c}{g}}\right)$$
(8)

It is an equation for calculating a relative altitude by correcting the pressure depending on temperature. T_0 is the



Fig. 1. Navigation information generation using a barometer.



Fig. 2. Altitude calculation using a barometer.

temperature at the initial altitude (absolute temperature), and $T_{gradient}$ is the temperature change depending on the altitude and has a constant value of 0.0065 [K/m]. Also, P_s is the pressure measured during the driving of a vehicle, P_{s0} is the initial pressure, and G_c is the gas constant (287.052 [J/K*kg]). Fig. 1 shows the entire process of calculating an altitude using a barometer (Lee 2013).

Based on the pressure and temperature measured at the initial position, the relative altitude for the pressure measured during driving was calculated. The final altitude was calculated by adding the initial altitude and the relative altitude. For the initial altitude, an average value of the altitude output of GNSS for one minute at a standstill was used; and the results are shown in Fig. 2.

A barometer is more sensitive to a change compared to GNSS altitude information, and thus, it can better represent the altitude change depending on the movement of a vehicle. However, a barometer is significantly affected by weather and temperature, and thus, the result varies depending on the environment.

The major error of a barometer includes conversion factor error. The altitude information of a vehicle from the barometer considering the error, P_{zw} can be expressed by the altitude obtained from the barometer, P_{zb} , and the conversion factor error, K_{zb} , as shown in Eq. (9).



Fig. 3. GNSS/INS/odometer/barometer integrated navigation system.

$$P_{zv} = P_{zb} + K_{zb} P_{zb} \tag{9}$$

As the barometer was installed at the interior of the vehicle, abrupt temperature change did not occur, and the initial pressure within the vehicle also did not change abruptly. Thus, the conversion factor error of the barometer could be modeled as a random constant. Based on odometer measurements, barometer measurements, and each error model, an integrated navigation system that added an odometer and a barometer to the GNSS/INS integrated navigation system was organized.

The GNSS/INS/odometer/barometer integrated navigation system consisted of the centralized Kalman filter as shown in Fig. 3, and it was implemented based on the 19th-order Kalman filter by adding the error models of the odometer and the barometer to the GNSS/INS integrated navigation system in Chapter 3. The system model can be expressed as Eq. (10).

$$\begin{bmatrix} \dot{x}_{_{DNS}} \\ \dot{x}_{_{o}} \\ \dot{x}_{_{b}} \end{bmatrix} = \begin{bmatrix} F_{_{DNS}} & 0_{_{15\times6}} \\ 0_{_{6\times15}} & 0_{_{6\times6}} \end{bmatrix} \begin{bmatrix} x_{_{DNS}} \\ x_{_{o}} \\ x_{_{h}} \end{bmatrix} + w_{_{CL}}, w_{_{CL}} \sim N(0, \mathcal{Q}_{_{CL}}) \quad (10)$$

where F_{INS} is the system model of the GNSS/INS integrated navigation system in Chapter 3; x_o is the odometer error state variable that consists of the conversion factor error, K_{xo} , and the non-alignment errors, $\delta \psi$, $\delta \theta$; x_h is the state variable that represents the conversion factor error of the barometer, K_{zb} ; and Q_{CL} represents the error covariances of INS, the odometer, and the barometer.

The measurement model of the GNSS/INS/odometer/ barometer uses all the GNSS, odometer, and barometer information, and thus it can be expressed as Eq. (11).



Fig. 4. Navigation system for vehicles (Softman S570).

$$z = \begin{bmatrix} P_{BNS} \\ V_{DNS} \\ V_{DNS} \\ P_{DNS} \end{bmatrix} - \begin{bmatrix} P_{GNSS} \\ V_{GNSS} \\ V_{n}^{*} \\ P_{h}^{*} \end{bmatrix} = H_{CL} \begin{bmatrix} x_{DNS} \\ x_{h} \\ x_{h} \end{bmatrix} + v_{CL}, v_{CL} \sim N(0, R_{CL}) \quad (11)$$

The measurement model, H_{CL} , in Eq. (19) is expressed as Eq. (12).

$$H_{cL} = \begin{bmatrix} I_{3\times3} & 0_{3\times3} & 0_{3\times3} & 0_{3\times6} & 0_{3\times3} & 0\\ 0_{3\times3} & I_{3\times3} & 0_{3\times3} & 0_{3\times6} & 0_{3\times3} & 0\\ 0_{3\times3} & I_{3\times3} & 0_{3\times3} & 0_{3\times6} & M & 0\\ 0 & 0 & 1 & 0_{1\times3} & 0_{1\times6} & 0_{1\times3} & 1 \end{bmatrix}$$
$$M = \begin{bmatrix} -c_{11}v_{x} & -c_{12}v_{x} & c_{13}v_{x}\\ -c_{21}v_{x} & -c_{22}v_{x} & c_{23}v_{x}\\ -c_{31}v_{x} & -c_{32}v_{x} & c_{33}v_{x} \end{bmatrix}$$
(12)

where c_{ij} is the component of the coordinate transformation matrix, C_b^n .

The GNSS/INS/odometer/barometer integrated navigation system can obtain a navigation solution that corrected the velocity error and altitude error of INS using an odometer and a barometer even in environments without GNSS information.

3. EXPERIMENT AND VERIFICATION

For the experiment environment, the Softman navigation device (Hyundai Mnsoft, http://www.hyundai-mnsoft.com) shown in Fig. 4 was used, and a barometer was separately installed at the vehicle. In the interior of the navigation device, MEMS triaxial accelerometer (AIS328DQ) and triaxial gyroscope (A3G4250D) from ST Company were installed. Also, the TESEOII GNSS receiver (ST Company)

Table 1. Specifications of the inertial sensors.

	AIS328DQ	A3G4250D
Measurement Range	±2.0 g	±250 dps
Sensitivity	1.81~2.12 mg/digit	7.4~10.1 mdps/digit
Noise density	100~600 µg/	0.03~0.15 dps/
Output rate	50 Hz	

Table 2. Specifications of the odometer and the GNSS receiver.

Odometer	TESEOII GNSS receiver		
Scale factor	900/637	Multi constellation	GPS GLONASS WAAS
Output rate		1 Hz	

Table 3. Specification of the barometer.

	LPS331AP
Measurement range (mbar)	260~1260
Pressure RMS noise (mbar)	0.02~0.450
Output rate (Hz)	1





Fig. 5. Experiment environment configuration.

was installed, and odometer information could be obtained through connection with the vehicle using an On-Board Diagnosis (DBD) cable. For the additionally installed barometer, MEMS barometer sensor (LPS331AP) from ST Company was used (Hyundai MnSoft, http://www.hyundaimnsoft.com).

Table 1 summarizes the specifications of the MEMS inertial sensors installed at Softman. Also, Table 2 summarizes the specifications of the odometer and the GNSS receiver, and Table 3 summarizes the specification of the barometer.

Using the above navigation device and barometer data, the entire experiment environment was organized as shown in Fig. 5. The sensor output of the navigation device was transmitted to a laptop in an Android environment. For the additionally installed barometer, STM32F103, which is micro controller unit, was additionally installed at the exterior, and the altitude was calculated by obtaining measurements using serial peripheral interface. The calculated altitude information was then transmitted to the laptop via serial communication. Based on this information, the final navigation solution was calculated by the laptop through the suggested integrated navigation algorithm.



Fig. 6. Driving path in Chungbuk National University.



Fig. 7. Results of the GNSS/INS and the GNSS/INS/odometer/barometer.

The driving experiment was performed in a driving path on campus shown in Fig. 6. The environment includes uphill roads, downhill roads, and speed bumps, and an area where GNSS signals are not available was made by disconnecting the GNSS antenna on a curved path. In the area where GNSS signals are not available, the error covariance matrix of the Kalman filter, P, was adjusted using the DOP value of the receiver so that improper estimation of the error correction for the sensor due to an abrupt change in the position value could be prevented.

Fig. 7 shows the results of the GNSS/INS and the GNSS/ INS/odometer/barometer based on the driving path on campus when there was no area where GNSS signals are not available. The red inverted triangle represents the GNSS output, the green dot represents the GNSS/INS/Odometer/ Barometer output, and the black star represents the GNSS/ INS output.

To examine the difference between the results of the

GNSS/INS and the GNSS/INS/odometer/barometer, the parts marked as circles 1 and 2 in Fig. 7 were magnified as shown in Fig. 8. It was found that the navigation solution calculated using the GNSS/INS/odometer/barometer was more accurate than that using the GNSS/INS.

To compare the two navigation solutions in an area where GNSS signals are not available, an area where GNSS signals are not available was made by arbitrarily disconnecting the GNSS antenna in a curved section within the same driving path, and the performance of the integrated navigation algorithm was examined.

As shown in the red rectangle in Fig. 9, an area where GNSS signals are not available was made for 20 seconds on the driving path in Chungbuk National University. Fig. 10 shows the results of the GNSS/INS and the GNSS/INS/ odometer/barometer integrated navigation system in the area where GNSS signals are not available. To examine the difference between the results of the GNSS/INS and the GNSS/INS/odometer/barometer, the part marked as a circle in Fig. 10 was magnified as shown in Fig. 11.



Fig. 8. Results of the GNSS/INS and the GNSS/INS/odometer/barometer (Magnified).



Fig. 9. Area where GNSS signals are not available in the driving path.



Fig. 10. Navigation system experiment results in the section where GNSS signals are not available.



Fig. 11. Navigation system experiment results in the section where GNSS signals are not available (Magnified).



Fig. 12. Altitude solutions of the two navigation systems.



Fig. 13. Altitude solutions of the two navigation systems (Magnified).

The difference between the position where the position of the navigation system was corrected by the re-reception of GNSS signals and the final position of the section where GNSS signals are not available corresponds to the cumulative position error that occurred during the omission of GNSS signals. Fig. 12 shows the altitude changes of each navigation system, and Fig. 13 shows the magnification of the GNSS outage section. The altitude solution of the GNSS/ INS had a large error since the error accumulated with time, but the GNSS/INS/Odometer/Barometer could calculate an altitude solution that has a smaller error than that of the GNSS/INS through altitude correction. Fig. 14 shows the changes in the two-dimensional navigation solution errors of the GNSS/INS and the GNSS/INS/Odometer/Barometer depending on time in the area where GNSS signals are not available.

Based on the above results, the distance between the final position solution in the area where GNSS signals are



Fig. 14. Two-dimensional horizontal errors of the two navigation systems.

Table 4. Cumulative errors in the area where GNSS signals are not available.

	GNSS/INS	GNSS/INS/ Odometer/Barometer
Horizontal Error (m)	101.2	23.85
Altitude Error (m)	15.19	1.28

not available for 23 seconds and the first position solution when GNSS signals were received was calculated for the two navigation systems as summarized in Table 4.

It was found that the GNSS/INS/odometer/barometer integrated navigation system could reduce the cumulative horizontal and altitude errors compared to the GNSS/INS integrated navigation system. This is thought to be because the odometer based on an encoder had a smaller error than the low-priced inertial sensor and thus the performance of the two-dimensional solution of the entire navigation system was improved, and because the divergence of the altitude information calculated based on the inertial sensor could be corrected using the barometer.

4. CONCLUSION

In this study, a GNSS/INS/odometer/barometer integrated navigation system that is equipped with lowpriced MEMS inertial sensor and GNSS receiver embedded in a commercial navigation device, the odometer of a vehicle, and a low-priced MEMS barometer was implemented, and the performance was verified.

INS using low-priced MEMS sensors can be used for a very short time, and thus, a GNSS/INS integrated navigation system using this would show performance deterioration in areas where GNSS signals are not available. Therefore, a GNSS/INS/odometer/barometer integrated navigation system based on the 19th-order Kalman filter was suggested by organizing a velocity correction system using an odometer that is basically installed at a vehicle and by organizing an altitude correction system using a barometer.

To examine the performance of the suggested system, a commercial navigation device and a barometer were installed at a vehicle and a driving test was performed in Chungbuk National University. Then, the results of the GNSS/INS integrated navigation system and the GNSS/INS/ odometer/barometer integrated navigation system were compared. An area where GNSS signals are not available was made by arbitrarily disconnecting the GNSS antenna for 20 seconds, and the comparison of the two navigation systems in the area where GNSS signals are not available showed that the GNSS/INS/odometer/barometer integrated navigation system had smaller cumulative errors regarding both the horizontal and altitude position solutions compared to the GNSS/INS integrated navigation system. In other words, it was found that a navigation solution that corrected the error of the GNSS/INS integrated navigation system to a certain degree in the area where GNSS signals are not available could be obtained based on the odometer and the barometer. It is thought that this could be used when a vehicle is operated in areas where GNSS signals are not available such as tunnels and underground roads.

ACKNOWLEDGMENTS

This study was supported by Hyundai Mnsoft, Inc.

REFERENCES

- Akim, E. L. & Tuchin, D. A. 2003, GPS errors statistical analysis for ground receiver measurements, Proc. of 17th International Symposium on Space Flight Dynamics; Preprint no.32, Keldysh IAM, RAS, Moscow
- Angrisano, A. 2010, GNSS/INS integration methods, Dottorato di ricerca (PhD) in Scienze Geodetiche e Topografiche Thesis, Universita'degli Studi di Napoli PARTHENOPE, Naple
- Bevly, D. M. & Cobb, S. 2010, GNSS for vehicle control (Norwood, MA: Artech House Inc.)
- Christensen, R. & Fogh, N. 2008, Inertial Navigation System, Department of Control Engineering, Aalborg University http://www.control.aau.dk/uav/reports/ 08gr1030a/08gr1030a_student_report.pdf
- Godha, S. 2006, Performance Evaluation of Low Cost MEMS-Based IMU Integrated with GPS for Land Vehicle

Navigation Application, Department of Geomatics Engineering, UCGE Reports 20239

- Jeon, C. W. & Lee, J. G. 1988, The Error Analysis of the Attitude Computation Algorithm for the SDINS, Journal of The Korean Society for Aeronautical & Space Sciences, 6, 50-58.
- Kim, Y. & Hwang, D. H. 2013, INS/Vision Integrated Navigation System Considering Error Characteristics of Landmark-Based Vision Navigation, Journal of Institute of Control, Robotics and Systems, 19, 95-101. http:// dx.doi.org/10.5302/J.ICROS.2013.19.2.095
- Kong, X. 2000, Inertial Navigation System Algorithm for Low Cost IMU, PhD Thesis, University of Sydney
- Lee, S. J. 2013, Performance Analysis of INS/Vision-sensor/ Barometer/Magnetometer Integrated Navigation System, MS Thesis, Konkuk University
- Nassar, S. 2003, Improving the Inertial Navigation System Error Model for INS and INS/DGPS Applications, UCGE Reports 20183
- Park, C. G., Kim, K. J., Park, H. W., & Lee, J. G. 1998, Development of an Initial Coarse Alignment Algorithm for Strapdown Inertial Navigation System, ICROS, Preprint
- Park, M. 2004, Error Analysis and Stochastic Modeling of MEMS based Inertial Sensors for Land Vehicle Navigation Applications, UCGE Reports 20194
- Seo, J., Lee, H. K., Lee, J. G., & Park, C. G. 2006, Lever Arm Compensation for GPS/INS/Odometer Integrated System, International Journal of Control, Automation and Systems, 4, 247-254.
- Trtterton, D. H. & Weston, J. L. 2004, Strapdown Inertial Navigation Technology (Reston, Virginia: Amer Inst of Aeronautics & Aircraft Design)



Jungi Park He received the B.S., M.S degrees in Electrical Engineering and Dept of Control and Robot Engineering from Chungbuk National University in 2013, 2015, respectively. His research interests include INS, Integrated Navigation System, AGV.



DongSun Lee She received the B.S, degrees in Electrical Engineering from Chungbuk National University in 2014, respectively. Currently, She is pursing her M.S., degrees in Chungbuk National University. Her research interests include INS, Heave compensation.



Chansik Park He received the B.S., M.S., and Ph.D. degrees in Electrical Engineering from Seoul National University in 1984, 1986 and 1997, respectively. He has been a Professor with the School of Electronics Engineering, Chungbuk National University, Cheongju, Korea, since 1997.

His research interests include GNSS, PNS, SDR, integer ambiguity resolution algorithm and Error Analysis.